

M 48

Core

Ribbon

width20 mm

height1000 mm

our certificates

OEKO
TEX

FSC

Logo's positions

FRONT:

Logo Logo Logo

Front: logo fitted

BACK:

ogo Logo Logo

Back: logo not fitted

Specs

24 mm
print area

2 mm
bleed area

Logo

15 mm logo max
height, centered

300 dpi

300 dpi minimal
image quality

TEXT

the smallest letter in the text
should be at least 1.5 mm high

Important

*All colours should be defined according to the Pantone MS scale for the coated papers (Pantone C)

*Projects should be prepared in vector graphics. We accept: Ai, EPS, SVG, PDF. Texts should be turned into curves.

T[®]

T-quality[®] new quality of ribbons in Europe

Certified materials
(Recycled, Oeko-Tex, GRS, FSC, Intertek, SMETA, PEFC, Flusta, Ecobabel, others)

Business sustainability

Buckles, safety breakers etc. are produced from recycled or renewable materials

Carbon footprint awareness

Code of Conduct responsible human resources

80% Green Energy used for production

Good waste management

Eco production

Made in Poland

Follow CSR

Front →

↓ 2 mm
bleed area

↓ 2 mm
bleed area

Logo Logo Logo Logo Logo Logo Logo Logo Logo Logo Logo Logo Logo Logo Logo Logo

← repetitive element →
repetitive element can be of any length

← repetitive element →
repetitive element can be of any length

← repetitive element →
repetitive element can be of any length

↓ 15 mm max
logo height

Back →

↓ 2 mm
bleed area

↓ 2 mm
bleed area

Logo Logo Logo Logo Logo Logo Logo Logo Logo Logo Logo Logo Logo Logo Logo Logo

← repetitive element →
repetitive element can be of any length

← repetitive element →
repetitive element can be of any length

← repetitive element →
repetitive element can be of any length

↓ 15 mm max
logo height

← 1000mm - total length of the tape →

(EN) Important - please read															
Manufacturer General Order Terms and Conditions of the Order.															
	</														